



Figure similar

22MM PLASTIC ROUND COMPLETE UNIT COMBINATION: INDICATOR LIGHT WITH SMOOTH LENSE ILLUMINATED WITH INTEGRATED LED 24V AC/DC SPRING-LOADED TERMINAL WITH HOLDER WHITE !!!  
 Phased-out product !!! SIRIUS ACT 3SU1 is successor Preferred successor type is >>3SU1102-6AA60-3AA0<<

<b>design of the product</b>	Complete unit round
<b>Enclosure</b>	
shape of the enclosure front	round
material of the enclosure	plastic
number of command points	0
<b>Actuator</b>	
design of the actuating element	indicator light
product extension optional light source	Yes
color of the actuating element	white
material of the actuating element	plastic
shape of the actuating element	Smooth lens
number of switching positions	0
<b>Front ring</b>	
product component front ring	No
<b>Holder</b>	
material of the holder	Plastic
<b>Contact block/ lampholder</b>	
socket design	integrated LED
number of lampholders	1
number of switching elements	0
<b>General technical data</b>	
product function	
• positive opening	No
• EMERGENCY STOP function	No
product component light source	Yes
protection class IP	IP66
vibration resistance acc. to IEC 60068-2-6	20 ... 200 Hz: 5g
reference code acc. to IEC 81346-2	P
Substance Prohibitance (Date)	01.07.2006 00:00:00
<b>Supply voltage</b>	
type of voltage of the supply voltage	
• of the light source	AC/DC
supply voltage of the light source at AC	
• at 50 Hz rated value	24 V
• at 60 Hz rated value	24 V
supply voltage 1 of the light source at DC rated value	24 V

relative negative tolerance of the supply voltage	-15 %
relative positive tolerance of the supply voltage	10 %
<b>Auxiliary circuit</b>	
number of NC contacts for auxiliary contacts	0
number of NO contacts for auxiliary contacts	0
number of CO contacts for auxiliary contacts	0
consumed current for rated value of supply voltage maximum	18 mA
<b>Connections/ Terminals</b>	
type of electrical connection	spring-loaded terminals
tightening torque of the screws in the bracket	1 ... 1.2 N·m
<b>Ambient conditions</b>	
ambient temperature	
• during operation	-25 ... +70 °C
• during storage	-40 ... +80 °C
environmental category during operation acc. to IEC 60721	3K6
<b>Installation/ mounting/ dimensions</b>	
fastening method	front mounting
shape of the installation opening	round
mounting diameter	22 mm
mounting height	11 mm
installation width	28 mm
installation depth	49 mm
<b>Accessories</b>	
product component holder for 3 switching elements	No
<b>Certificates/ approvals</b>	
General Product Approval	Declaration of Conformity



[Miscellaneous](#)



Marine / Shipping

other



[Confirmation](#)

other

Railway

[Miscellaneous](#)

[Special Test Certificate](#)

#### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=3SB3244-6AA60-0CC0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mfb=3SB3244-6AA60-0CC0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB3244-6AA60-0CC0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)  
[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SB3244-6AA60-0CC0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB3244-6AA60-0CC0&lang=en)

last modified:

1/18/2021 