



LOGO!Power/1AC/24VDC/1.3A

LOGO!POWER 24 V / 1.3 A Stabilized power supply input: 100-240 V AC
output: DC 24 V / 1.3 A

Input	
Input	1-phase AC or DC
Rated voltage value V_{in} rated	100 ... 240 V
Voltage range AC	85 ... 264 V
input voltage	
• at DC	110 ... 300 V
Wide-range input	Yes
Overvoltage resistance	300 V AC for 1 s
Mains buffering	at $V_{in} = 187$ V
Mains buffering at I_{out} rated, min.	40 ms; at $V_{in} = 187$ V
Rated line frequency 1	50 Hz
Rated line frequency 2	60 Hz
Rated line range	47 ... 63 Hz
input current	
• at rated input voltage 120 V	0.7 A
• at rated input voltage 230 V	0.35 A
Switch-on current limiting (+25 °C), max.	25 A
I^2t , max.	0.8 A ² ·s
Built-in incoming fuse	internal
Protection in the mains power input (IEC 898)	Recommended miniature circuit breaker: from 6 A characteristic B or from 2 A characteristic C
Output	
Output	Controlled, isolated DC voltage
Rated voltage V_{out} DC	24 V
• output voltage at output 1 at DC rated value	24 V
Total tolerance, static ±	3 %
Static mains compensation, approx.	0.1 %
Static load balancing, approx.	0.1 %
Residual ripple peak-peak, max.	200 mV
Residual ripple peak-peak, typ.	30 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	300 mV
Spikes peak-peak, typ. (bandwidth: 20 MHz)	50 mV
Adjustment range	22.2 ... 26.4 V
product function output voltage adjustable	Yes
Output voltage setting	via potentiometer
Status display	Green LED for output voltage OK
On/off behavior	No overshoot of V_{out} (soft start)
Startup delay, max.	0.5 s
Voltage rise, typ.	100 ms

Rated current value I _{out} rated	1.3 A
Current range	0 ... 1.3 A
<ul style="list-style-type: none"> Note 	+55 ... +70 °C: Derating 2%/K
supplied active power typical	31.2 W
Parallel switching for enhanced performance	Yes
Numbers of parallel switchable units for enhanced performance	2
Efficiency	
Efficiency at V _{out} rated, I _{out} rated, approx.	86 %
Power loss at V _{out} rated, I _{out} rated, approx.	5 W
power loss [W] during no-load operation maximum	0.3 W
Closed-loop control	
Dynamic mains compensation (V _{in} rated ±15 %), max.	0.2 %
Dynamic load smoothing (I _{out} : 10/90/10 %), U _{out} ± typ.	1 %
Load step setting time 10 to 90%, typ.	1 ms
Load step setting time 90 to 10%, typ.	1 ms
Protection and monitoring	
Output overvoltage protection	Yes, according to EN 60950-1
Current limitation, typ.	1.7 A
property of the output short-circuit proof	Yes
Short-circuit protection	Constant current characteristic
enduring short circuit current RMS value	
<ul style="list-style-type: none"> maximum 	1.7 A
overcurrent overload capability in normal operation	overload capability 150% I _{out} rated typ. 200 ms
Overload/short-circuit indicator	-
measuring point for output current	50 mV = [^] 1.3 A
overcurrent overload capability when switching on	150% I _{out} rated typ. 200 ms
Safety	
Primary/secondary isolation	Yes
galvanic isolation	Safety extra-low output voltage U _{out} acc. to EN 60950-1 and EN 50178
Protection class	Class II (without protective conductor)
Degree of protection (EN 60529)	IP20
Approvals	
CE mark	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cURus-Recognized (UL 60950, CSA C22.2 No. 60950), File E151273, NEC class 2 (acc. to UL 1310)
certificate of suitability NEC Class 2	Yes
CB approval	Yes
certificate of suitability EAC approval	Yes
Marine approval	ABS, BV, DNV GL, LRS
EMC	
Emitted interference	EN 55022 Class B
Supply harmonics limitation	not applicable
Noise immunity	EN 61000-6-2
environmental conditions	
ambient temperature	
<ul style="list-style-type: none"> during operation 	-25 ... +70 °C
<ul style="list-style-type: none"> Note 	with natural convection
<ul style="list-style-type: none"> during transport 	-40 ... +85 °C
<ul style="list-style-type: none"> during storage 	-40 ... +85 °C
Humidity class according to EN 60721	Climate class 3K3, 5 ... 95% no condensation
Mechanics	
Connection technology	screw-type terminals
Connections	
<ul style="list-style-type: none"> Supply input 	L, N: 1 screw terminal each for 0.5 ... 2.5 mm ² single-core/finely stranded
<ul style="list-style-type: none"> Output 	+, -: 1 screw terminal each for 0.5 ... 2.5 mm ²
<ul style="list-style-type: none"> Auxiliary 	-
width of the enclosure	36 mm

height of the enclosure	90 mm
depth of the enclosure	53 mm
required spacing	
• top	20 mm
• bottom	20 mm
• left	0 mm
• right	0 mm
Weight, approx.	0.12 kg
product feature of the enclosure housing can be lined up	Yes
Installation	Snaps onto DIN rail EN 60715 35x7.5/15, direct mounting in different mounting positions
MTBF at 40 °C	3 094 996 h
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

